

Leidingdrager Armaflex FX4

Leidingdrager AF-FX4 isolatiedikte 15,5 mm - 22,5 mm

Max. buiten-Ø buis [mm]	[maat]	Buiten-Ø incl. isolatie [mm]	Lengte [mm]	Max. toel. afstand [m]	Gewicht [kg/st]	VPE [st]	Artikelnr.
22 - 25	½	60 - 64	55	2,75	0,035	28	FX422/25
28 - 30	¾	66 - 70	55	3,00	0,041	28	FX428/30
35 - 38	1	74 - 79	65	3,50	0,057	24	FX435-38
42 - 45	1¼	85 - 88	65	3,75	0,062	24	FX442/45
48	1½	91	65	4,25	0,070	24	FX448
54 - 57		98 - 101	65	4,25	0,074	24	FX454/57
60 - 64	2	105 - 109	75	4,75	0,093	20	FX460/64
76 - 80	2½	122 - 127	85	5,50	0,135	16	FX476/80
89	3	136	100	6,00	0,226	12	FX489
110 - 114	4	162	115	6,00	0,276	12	FX4114
133 - 140	DN125	183 - 189	115	6,00	0,341	12	FX4133/140
160		210	115	6,00	0,430	6	FX4160
165 - 168	DN150	216 - 219	125	6,00	0,456	6	FX4165/168
216 - 219	DN200	267- 270	170	6,00	0,806	4	FX4216/219
267 - 273	DN250	318 - 324	170	6,00	1,074	3	FX4267/273
324	DN300	375	215	4,50	1,443	1	FX4324

Bijbehorende lichte beugel voor leidingdrager AF-FX4

Artikelnr. Leidingdrager	Omschrijving leidingdrager	Artikelnr. lichte beugel	Omschrijving bijbehorende beugel	Ø
FX422/25	Leidingdrager AF FX-4, 22-25 mm	M0426522	Trabant beugel, 57- 61 mm, M8/10	60
FX428/30	Leidingdrager AF FX-4, 28-30 mm	M0426582	Trabant beugel, 63- 67 mm, M8/10	66
FX435-38	Leidingdrager AF FX-4, 35-38 mm	M0426652	Trabant beugel, 69- 74 mm, M8/10	74
FX442/45	Leidingdrager AF FX-4, 42-45 mm	M0426722	Trabant beugel, 76- 85 mm, M8/10	85
FX448	Leidingdrager AF FX-4, 48 mm	M0426772	Trabant beugel, 84- 90 mm, M8/10	91
FX454/57	Leidingdrager AF FX-4, 54-57 mm	M0370099	Beugel Omnia MB, 96-101 mm, M8/10	101
FX460/64	Leidingdrager AF FX-4, 60-64 mm	M0370105	Beugel Omnia MB, 102-108 mm, M8/10	105
FX476/80	Leidingdrager AF FX-4, 76-80 mm	M0427142	Trabant beugel, 114-122 mm, M8/10	122
FX489	Leidingdrager AF FX-4, 89 mm	H3985750	Flamco beugel, 131-136 mm, M8/10	136
FX4114	Leidingdrager AF FX-4, 110-114 mm	H3986250	Flamco beugel, 164-169 mm, M8/10	162
FX4133/140	Leidingdrager AF FX-4, 133-140 mm	H3986350	Flamco beugel, 183-189 mm, M8/10	189

Bijbehorende zware beugel voor leidingdrager AF-FX4

Artikelnr. Leidingdrager	Omschrijving leidingdrager	Artikelnr. zware beugel	Omschrijving bijbehorende beugel	Ø
FX422/25	Leidingdrager AF FX-4, 22-25 mm	M0068863	Max PSM beugel, 57-61 mm, M 8/M10	60
FX428/30	Leidingdrager AF FX-4, 28-30 mm	M0068882	Max PSM beugel, 63-67 mm, M 8/M10	66
FX435-38	Leidingdrager AF FX-4, 35-38 mm	M00880769	Max PSM beugel, 70-76 mm, M 8/M10	74
FX442/45	Leidingdrager AF FX-4, 42-45 mm	M0088093	Max PSM beugel, 84-90 mm, M10/M12	85
FX448	Leidingdrager AF FX-4, 48 mm	M0088093	Max PSM beugel, 84-90 mm, M10/M12	91
FX454/57	Leidingdrager AF FX-4, 54-57 mm	M0088105	Max PSM beugel, 96-102 mm, M10/M12	101
FX460/64	Leidingdrager AF FX-4, 60-64 mm	M0088105	Max PSM beugel, 96-102 mm, M10/M12	105
FX476/80	Leidingdrager AF FX-4, 76-80 mm	M0088125	Max PSM beugel, 120-124 mm, M10/M12	122
FX489	Leidingdrager AF FX-4, 89 mm	M0088138	Max PSM beugel, 132-137 mm, M10/M12	136
FX4114	Leidingdrager AF FX-4, 110-114 mm	M0088164	Max PSM beugel, 157-162 mm, M10/M12	162
FX4133/140	Leidingdrager AF FX-4, 133-140 mm	M0088194	Max PSM beugel, 189-193 mm, M10/M12	189
FX4160	Leidingdrager AF FX-4, 160 mm	M0088216	Max PSM beugel, 210-215 mm, M10/M12	210
FX4165/168	Leidingdrager AF FX-4, 165-168 mm	M0088228	Max PSM beugel, 219-225 mm, M10/M12	219
FX4216/219	Leidingdrager AF FX-4, 216-219 mm	M0088274	Max PSM beugel, 269-273 mm, M10/M12	270
FX4267/273	Leidingdrager AF FX-4, 267-273 mm	M0066955	Titan HD beugel, 324mm, M12	324
FX4324	Leidingdrager AF FX-4, 324 mm	M0066983	Titan HD beugel, 375mm, M12	375