

## HSS-G plaatwerkboor geslepen DIN1897 Silver-Line



Type N korte geslepen uitvoering, genitreerd, tophoek 135°.  
 Toepassing: voor het boren in de meest voorkomende plaatstaal materialen.

De spiraallengte staat vermeld per boor.

| Artikelnr. | Boor Ø [mm] | Spiraallengte [mm] | Totaallengte [mm] | Verpakking |
|------------|-------------|--------------------|-------------------|------------|
| 34304      | 3,0         | 16                 | 46                | 10         |
| 34314      | 3,1         | 18                 | 49                | 10         |
| 34324      | 3,2         | 18                 | 49                | 10         |
| 34345      | 3,4         | 20                 | 52                | 10         |
| 34355      | 3,5         | 20                 | 52                | 10         |
| 34405      | 4,0         | 22                 | 55                | 10         |
| 34415      | 4,1         | 22                 | 55                | 10         |
| 34425      | 4,2         | 22                 | 55                | 10         |
| 34455      | 4,5         | 24                 | 58                | 10         |
| 34486      | 4,8         | 26                 | 62                | 10         |
| 34506      | 5,0         | 26                 | 62                | 10         |
| 34526      | 5,2         | 26                 | 62                | 10         |
| 34556      | 5,5         | 28                 | 66                | 10         |
| 34606      | 6,0         | 28                 | 66                | 10         |
| 34657      | 6,5         | 31                 | 70                | 10         |
| 34707      | 7,0         | 34                 | 74                | 10         |
| 34807      | 8,0         | 37                 | 79                | 10         |
| 34857      | 8,5         | 37                 | 79                | 10         |