

## HSS spiraalboor DIN 338 type N Silver-Line



Rolgewalste uitvoering, genitreerd, tophoek 118°.  
 Algemeen gebruik, voor het boren in de meest voorkomende materialen, zoals staal en gietijzer.

De spiraallengte staat vermeld per boor.

Artikelnr.	Boor Ø [mm]	Spiraallengte [mm]	Totaallengte [mm]	Verpakking
34004	0,4	5	20	10
34005	0,5	6	22	10
34010	1,0	12	34	10
34015	1,5	18	40	10
34020	2,0	24	49	10
34024	2,4	30	57	10
34025	2,5	30	57	10
34026	2,6	30	57	10
34030	3,0	33	61	10
34032	3,2	36	65	10
34033	3,3	36	65	10
34034	3,4	39	70	10
34035	3,5	39	70	10
34036	3,6	39	70	10
34037	3,7	39	70	10
34038	3,8	43	75	10
34039	3,9	43	75	10
34040	4,0	43	75	10
34041	4,1	43	75	10
34042	4,2	43	75	10
34044	4,4	47	80	10
34045	4,5	47	80	10

Artikelnr.	Boor Ø [mm]	Spiraallengte [mm]	Totaallengte [mm]	Verpakking
34048	4,8	52	86	10
34050	5,0	52	86	10
34052	5,2	52	86	10
34055	5,5	57	93	10
34058	5,8	57	93	10
34060	6,0	57	93	10
34062	6,2	63	101	10
34065	6,5	63	101	10
34068	6,8	69	109	10
34070	7,0	69	109	10
34072	7,2	69	109	10
34075	7,5	69	109	10
34080	8,0	75	117	10
34085	8,5	75	117	10
34090	9,0	81	125	10
34095	9,5	81	125	10
34100	10,0	87	133	10
34105	10,5	87	133	5
34110	11,0	94	142	5
34115	11,5	94	142	5
34120	12,0	101	151	5
34125	12,5	101	151	5

## HSS spiraalboor DIN 338 type N Silver-Line

Met afgedraaide cilindrische schacht.



Artikelnr.	Boor Ø [mm]	Spiraallengte [mm]	Totaallengte [mm]	Af-gdraaid [mm]	Verpakking
34130	13,0	101	151	10	5
34135	13,5	108	160	13	5
34140	14,0	108	160	13	1
34150	15,0	114	169	13	1
34160	16,0	120	178	13	1
34170	17,0	125	184	13	1
34180	18,0	130	191	13	1
R1212000	20,0	140	205	10	1
34210	21,0	145	215	13	1
34220	22,0	145	215	13	1