

Kabelbinders



Kabelbinders

Materiaal: Polyamide 6.6
 Kleur: Transparant / zwart (UV bestendig)
 Temperatuur bereik: -40 °C tot + 85 °C
 Ontvlambaarheid: UL 94 V2 (V0 beschikbaar)
 Normering: UL E75050, Lloyd's, GL 59425-08HH, Mil-23190D

Artikelnr.	Lengte [mm]	Kleur	Breedte [mm]	Max. bundel Ø [mm]	Trekkracht [kg]	Verpakking
OVD6848	200	Zwart	2,5	53	8,1	100
OVD6849	300	Zwart	3,6	76	18,2	100
OVD5781	200	Zwart	4,8	50	22,2	100
OVD5783	300	Zwart	4,8	76	22,2	100
OVD5431	300	Transparant	4,8	76	22,2	100
OVD5784	370	Zwart	4,8	102	22,2	100
OVD5785	370	Transparant	4,8	102	22,2	100
OVD6283	450	Zwart	7,6	132	54,4	100
OVD1980	530	Transparant	9,0	140	79,4	100
OVD1882	775	Transparant	9,0	228	79,4	100
OVD2681	920	Transparant	9,0	263	79,4	100
OVD3579	1220	Transparant	9,0	365	79,4	100
OVD7263	480	Zwart	12,6	120	114,0	100

